



**Document of Performance  
According to Regulation (EU) 305/2011**

|   |   |                |
|---|---|----------------|
| Aduro 8   |   | PoD No: 8 0010 |
| Roomheater burning solid fuel <u>without</u> hot water supply.<br>EN 13240:2001/A2:2004/AC:2007   |   |                |
| Aduro AS, Beringvej 17, DK-8361 Hasselager, Denmark. <a href="http://www.aduro.dk">www.aduro.dk</a> , <a href="mailto:info@aduro.dk">info@aduro.dk</a> , Tel.: +45 70274703.  |   |                |
| System 3 of assessment and verification of constancy of performance of the construction product: Internal quality security system in combination with external production control.  |   |                |
| Rhein-Ruhr Feuerstätten Prüfstelle GmbH, Im Lipperfeld 34 b, D-46047 Oberhausen, notified body number: 1625 and<br>Teknologisk Institut, Kongsvang 29, DK-8000 Aarhus, notified body number: 300.<br><br>performed the determination of the product type on the basis of type testing under system 3 and issued test report:<br>RRF- 40 10 2466<br>300-ELAB-1072-NS |   |                |
| Declared performance  |   |                |
| <b>Harmonized technical specification</b>   | EN 13240:2001/A2:2004/AC:2007   |                |
| <b>Essential characteristics</b>  | <b>Performance</b>  |                |
| <b>Fire safety</b>  |   |                |
| Reaction to fire  | A1  |                |
| Distance to combustible materials<br>Distance marked with * is for installation with isolated pipe  | Minimum distances, in mm<br>rear = 200/*100<br>sides = 300<br>front = 850 |                |
| Risk of burning fuel falling out  | Pass  |                |
| <b>Emission of combustion products</b>  | CO[0.10 %]  |                |
| <b>Surface temperature</b>  | Pass  |                |
| <b>Electrical safety</b>  | NPD   |                |
| <b>Cleanability</b>   | Pass  |                |
| <b>Maximum water operating pressure</b>   | NPD   |                |
| <b>Flue gas temperature at nominal heat output</b>  | T [293 °C]  |                |
| <b>Mechanical resistance (to carry a chimney/flue)</b>  | NPD   |                |
| <b>Thermal output</b>   |   |                |
| Nominal heat output   | 5 kW  |                |
| Room heating output   | 5 kW  |                |
| Water heating output  | " kW  |                |
| <b>Energy efficiency</b>  | $\eta$ [80,5 %]   |                |

Signed for and on behalf of the manufacturer by:

Christian Skovbo, CEO, Aduro AS  
Hasselager, 24-06-2013

Aduro A/S  
Beringvej 17  
DK-8361 Hasselager  
Tel.: +45 70274703  
Fax: +45 70274704  
CVR-nr. 28488602